

Specification	Model	
	12V-180DC	
DC output voltage	12V	
Output voltage range(Note:2)	1%	
Rated output current	15A	
Wave and noise(Note:3)	100mVp-p	
Inlet stability(Note:4)	0.30%	
Load stability(Note:5)	0.30%	
DC output power	180W	
Efficiency	85.50%	
Adjustable range for DC voltage	0-14.2V	
Input Voltage Range	85 ~ 132VAC/180 ~ 264VAC 47-63Hz ; 255-370VDC	
Input current	3.2A/115v 1.6A/230V	
AC inrush current	35A/115V 60A/230V	
Leakage current	< 1mA/240VAC	
Overload protection	125% ~ 165%	
Temperature coefficient	0.03%/°C (0 ~ 50°C)	
Setup, rise , hold up time	100ms,50ms,20ms	
Vibration	10 ~ 500Hz,2G 10min,/1 cycle , time 60 minutes	
Working temperature and humidity	-10°C ~ 60°C,20% ~ 90%RH	
Storage temperature and humidity	-20°C ~ 85°C,10% ~ 95%RH	
Size	199*98*42mm	
Weight	0.7Kgs	
Safety standards	UL1012TUV 60950 (IEC950 , UL1950) Certificate	
EMC Standard	CISPR22 (55022) IEC801-2 , 3 , 4IEC555-2 Certificate	